

Product Category	Model #	Thermostat Type	Approximate Temperature	Container Volume Size	Container Dimensions	Cord Type	Voltage	Wattage (+/-5%)	Amps (+/-5%)	Approximate Weight	
Bucket Heaters	BH05RR	Internal Preset Temperature	100° F (+-5° F) / 38° C (+-3° C)	05 Gallon / 19 L	11.8"D x 15.6"H	15 AMP Plug	120V	60 / 120	.5 / 1	4 lbs / 2 kg	
	BH05PRO	Digital Thermostatic Controller	145° F (+-5° F) / 63° C (+-3° C)	06 Gallon / 19 L	11.8"D x 15.6"H	15 AMP Plug	120V	160	1.33	6 lbs / 3 kg	
	BH15RR	Internal Preset Temperature	100° F (+-5° F) / 38° C (+-3° C)	15 Gallon / 57 L	14.4"D x 26.3"H	15 AMP Plug	120V	160 / 320	1.33 / 2.67	7 lbs / 3 kg	
	BH15PRO	Digital Thermostatic Controller	145° F (+-5° F) / 63° C (+-3° C)	15 Gallon / 57 L	14.4"D x 26.3"H	15 AMP Plug	120V	400	3.33	9 lbs / 4 kg	
	BH30RR	Internal Preset Temperature	100° F (+-5° F) / 38° C (+-3° C)	30 Gallon / 114 L	19.4"D x 29.5"H	15 AMP Plug	120V	280 / 560	2.33 / 4.67	9 lbs / 4 kg	
Drum Heaters	BH30PRO	Digital Thermostatic Controller	145° F (+-5° F) / 63° C (+-3° C)	30 Gallon / 114 L	19.4"D x 29.5"H	15 AMP Plug	120V	720	6	11 lbs / 5 kg	
	BH55RR	Internal Preset Temperature	100° F (+-5° F) / 38° C (+-3° C)	55 Gallon / 208 L	23.3"D x 34.9"H	15 AMP Plug	120V	400 / 800	3.33 / 6.67	11 lbs / 5 kg	
	BH55PRO	Digital Thermostatic Controller	145° F (+-5° F) / 63° C (+-3° C)	55 Gallon / 208 L	23.3"D x 34.9"H	15 AMP Plug	120V	800	6.67	13 lbs / 6 kg	
	BH275	Digital Thermostatic Controller	145° F (+-5° F) / 63° C (+-3° C)	275 Gallon / 1040 L	48" L x 40" W x 46" H	15 AMP Plug	120V	1440	12	41 lbs / 19 kg	
	TH330	Digital Thermostatic Controller	145° F (+-5° F) / 63° C (+-3° C)	330 Gallon / 1250 L	48" L x 40" W x 53" H	15 AMP Plug	120V	1440	12	45 lbs / 20 kg	
DEF Tote Heaters	TH275DG	Digital Thermostatic Controller	70° F (+-5° F) / 21° F (+-3° C)	275 Gallon / 1040 L	48" L x 40" W x 46" H	15 AMP Plug	120V	1440	12	100 lbs / 45 kg	
	TH330DG	Digital Thermostatic Controller	70° F (+-5° F) / 21° F (+-3° C)	330 Gallon / 1250 L	48" L x 40" W x 53" H	15 AMP Plug	120V	1440	12	105 lbs / 47 kg	
Hot Box	HB64	Digital Thermostatic Controller	120° F (+-10° F) / 49° C (+-5° C)	N/A	4" L x 4" W x 4" H	15 AMP Plug	120V	1440	12	60 lbs / 27 kg	
	FBW60	Internal Preset Temperature	110° F (+-10° F) / 43° C (+-5° C)	600 board foot box	Single Cylinder	15 AMP Plug	120V	280	2.33	8 lbs / 4 kg	
Foam Box Heaters	FBW15	Internal Preset Temperature	110° F (+-10° F) / 43° C (+-5° C)	200 board foot box	Disposable Box	15 AMP Plug	120V	280	2.33	8 lbs / 4 kg	
	FCW1212C	Internal Preset Temperature	80° F (+-10° F) / 26° C (+-5° C)	600 board foot cylinder	12"D x 15"H / 32 cm x 46 cm	15 AMP Plug	120V	95	0.79	4 lbs / 2 kg	
Foam Cylinder Heaters	FCW1525C	Internal Preset Temperature	80° F (+-10° F) / 26° C (+-5° C)	17 Gallon Cylinder	15"D x 27"H / 38 cm x 69 cm	15 AMP Plug	120V	400	3.33	6 lbs / 3 kg	
	FCW2428C	Internal Preset Temperature	80° F (+-10° F) / 26° C (+-5° C)	60 Gallon Cylinder	24"D x 34"H / 61 cm x 87 cm	15 AMP Plug	120V	550	4.58	8 lbs / 4 kg	
	FCW1541	Internal Preset Temperature	80° F (+-10° F) / 26° C (+-5° C)	27 Gallon Cylinder	15"D x 44"H / 38 cm x 112 cm	15 AMP Plug	120V	720	6	12 lbs / 6 kg	
	FCW15H	N/A	N/A	Insulated Hood 17/27 gal. cylinder	Insulated Hood 17/27 gal. cylinder	N/A	N/A	N/A	N/A	2 lbs / 1 kg	
	GCW20	Internal Preset Temperature	90° F (+-5° F) / 32° C (+-3° C)	20 lb Tank	12.5"D x 18"H / 32 cm x 46 cm	15 AMP Plug	120V	120	1	4 lbs / 2 kg	
Gas Cylinder Heaters	GCW30	Internal Preset Temperature	90° F (+-5° F) / 32° C (+-3° C)	30 lb Tank	12.5"D x 24"H / 32 cm x 61 cm	15 AMP Plug	120V	160	1.33	6 lbs / 3 kg	
	GCW40	Internal Preset Temperature	90° F (+-5° F) / 32° C (+-3° C)	40 lb Tank	12.5"D x 29"H / 32 cm x 74 cm	15 AMP Plug	120V	280	2.33	8 lbs / 4 kg	
	GCW100	Internal Preset Temperature	90° F (+-5° F) / 32° C (+-3° C)	100 lb Tank	14.5"D x 48"H / 37 cm x 122 cm	15 AMP Plug	120V	560	4.67	12 lbs / 6 kg	
	GCW420	Internal Preset Temperature	90° F (+-5° F) / 32° C (+-3° C)	420 lb Tank	30"D x 82"H / 76 cm x 132 cm	15 AMP Plug	120V	960	8	18 lbs / 8 kg	
	GCW500	Internal Preset Temperature	90° F (+-5° F) / 32° C (+-3° C)	500 Gallon Tank	38"D x 81"H / 96 cm x 300 cm	2 - 15 AMP Plugs	120V	1600	13.33	40 lbs / 18 kg	
Concrete Curing Blankets	GCW1K	Internal Preset Temperature	90° F (+-5° F) / 32° C (+-3° C)	1000 Gallon Tank	41"D x 192"L / 104 cm x 488 cm	2 - 15 AMP Plugs	120V	2880	24	50 lbs / 23 kg	
	MD1020	Internal Preset Temperature	10° x 20' / 3m x 6m	12' x 22' / 3.66 m x 6.7 m	200 sq ft / 18.6 sq m	30 AMP Plug	120V	2400	20	100 lbs / 46 kg	
	MD1010	Internal Preset Temperature	10° x 10' / 3m x 3m	12' x 12' / 3.66 m x 3.66 m	100 sq ft / 9.3 sq m	15 AMP Plug	120V	1440	12	50 lbs / 23 kg	
	MD0520	Internal Preset Temperature	5' x 20' / 1.5m x 6m	6' x 21' / 1.8 m x 6.4 m	100 sq ft / 9.3 sq m	15 AMP Plug	120V	1440	12	50 lbs / 23 kg	
	MD0510	Internal Preset Temperature	5' x 10' / 1.5m x 3m	6' x 11' / 1.8 m x 3.4 m	50 sq ft / 4.6 sq m	15 AMP Plug	120V	720	6	25 lbs / 12 kg	
	MD0320	Internal Preset Temperature	3' x 20' / 1m x 6m	4' x 21' / 1.2 m x 6.4 m	60 sq ft / 5.6 sq m	15 AMP Plug	120V	960	8	30 lbs / 14 kg	
	MD0310	Internal Preset Temperature	3' x 10' / 1m x 3m	4' x 11' / 1.2 m x 3.4 m	30 sq ft / 2.8 sq m	15 AMP Plug	120V	480	4	15 lbs / 7 kg	
	MD0304	Internal Preset Temperature	3' x 4' / 1m x 1.2m	4' x 5' / 1.2 m x 1.5 m	12 sq ft / 1.1 sq m	15 AMP Plug	120V	240	2	6 lbs / 3 kg	
	MD0404-12V	Internal Preset Temperature	4' x 4' / 1.21m x 1.21m	4' x 4' / 1.21 m x 1.21 m	8 sq ft / .74 sq m	15 AMP Plug	12V	280	23.33	3 lbs / 1.5 kg	
	MD0202-12V	Internal Preset Temperature	2' x 2' / .61m x .61m	2' x 2' / .61 m x .61 m	4 sq ft / .4 sq m	15 AMP Plug	12V	95	7.92	3 lbs / 1.5 kg	
	Ground Thawing Blankets	EH0308	Internal Preset Temperature	5' x 9' / 1.5m x 2.8m	6' x 10' / 1.8 m x 3 m	45 sq ft / 4.2 sq m	20 AMP Plug	120V	1650	13.75	25 lbs / 12 kg
		EH0325	Internal Preset Temperature	3' x 25' / 1m x 7.6m	4' x 26' / 1.2 m x 7.9 m	75 sq ft / 7 sq m	30 AMP Plug	120V	2750	22.92	38 lbs / 18 kg
EH0310		Internal Preset Temperature	3' x 10' / 1m x 3m	4' x 11' / 1.2 m x 3.4 m	30 sq ft / 2.8 sq m	15 AMP Plug	120V	1100	9.17	15 lbs / 7 kg	
EH0304		Internal Preset Temperature	3' x 4' / 1m x 1.2m	4' x 5' / 1.2 m x 1.5 m	12 sq ft / 1.1 sq m	15 AMP Plug	120V	400	3.33	6 lbs / 3 kg	
EH0202		Internal Preset Temperature	2' x 2' / .61m x .61m	2' x 2' / .61 m x .61 m	4 sq ft / .4 sq m	15 AMP Plug	120V	95	0.79	3 lbs / 1.5 kg	
EH0202DV	Internal Preset Temperature	2' x 2' / .61m x .61m	2' x 2' / .61 m x .61 m	4 sq ft / .4 sq m	15 AMP Plug	120V/12V	95	7.92 / 0.79	3 lbs / 1.5 kg		

(CERTIFIED TO UL/CSA/CE STANDARDS)
 Additional specifications available including: 240 VAC and QIDZ, Class I, Division 2 Groups A through D, T4 
 Powerblanket reserves the right to improve product and change specification without notification.
 * All temperatures may vary based on boundary conditions.

Product Category	Model #	Thermostat Type	Approximate Product Temperature	Nominal Pipe Diameter	Blanket Length	Cord Type	Voltage	Wattage (+-5%)	Amps (+-5%)	Weight
Pipe Heaters	PH040505G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	4-5" / 10-12 cm	5' / 1.5 m	15 AMP Plug	120V	120 / 320	1.33 / 2.67	100 lbs / 46 kg
	PH040510G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	4-5" / 10-12 cm	10' / 3.0 m	15 AMP Plug	120V	360 / 720	3.00 / 6.00	50 lbs / 23 kg
	PH040520G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	4-5" / 10-12 cm	20' / 6.0 m	15 AMP Plug	120V	720 / 1440	6.00 / 12.00	50 lbs / 23 kg
	PH060605G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	6" / 15 cm	5' / 1.5 m	15 AMP Plug	120V	280 / 560	2.33 / 4.67	25 lbs / 12 kg
	PH060610G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	6" / 15 cm	10' / 3.0 m	15 AMP Plug	120V	550 / 1100	4.58 / 9.17	15 lbs / 7 kg
	PH060620G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	6" / 15 cm	20' / 6.0 m	20 AMP Plug	120V	960 / 1920	8.00 / 16.00	30 lbs / 14 kg
	PH080805G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	8" / 20 cm	5' / 1.5 m	15 AMP Plug	120V	360 / 720	3.00 / 6.00	15 lbs / 7 kg
	PH080810G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	8" / 20 cm	10' / 3.0 m	15 AMP Plug	120V	720 / 1440	6.00 / 12.00	6 lbs / 3 kg
	PH080820G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	8" / 20 cm	20' / 6.0 m	30 AMP Plug	120V	1440 / 2880	12.00 / 24.00	3 lbs / 1.5 kg
	PH101005G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	10" / 25 cm	5' / 1.5 m	15 AMP Plug	120V	400 / 800	3.33 / 6.67	3 lbs / 1.5 kg
PH101010G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	10" / 25 cm	10' / 3.0 m	20 AMP Plug	120V	900 / 1800	7.50 / 15.00	15 lbs / 7 kg	
PH121205G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	12" / 30 cm	5' / 1.5 m	15 AMP Plug	120V	480 / 960	4.00 / 8.00	15 lbs / 7 kg	
PH121210G	Internal Preset Temperature	90° F (+- 5° F) / 32°C (+-3° C)	12" / 30 cm	10' / 3.0 m	15 AMP Plug	120V	960 / 1920	8.00 / 16.00	6 lbs / 3 kg	

(CERTIFIED to UL/CSA/CE STANDARDS) Additional specifications available including: 240 VAC and CID2. Class 1 Division 2 Groups A through D. T4  Powerblanket reserves the right to improve product and change specification without notification. * All temperatures may vary based on boundary conditions.